







| 产品名称 | 规格 | | 图片 |
|-----------------------|---------------------|--|---|
| 标准 洛氏 硬度块 | 60-70HRC | |  |
| | 50-55HRC | | |
| | 40-50HRC | | |
| | 30-35HRC | | |
| | 20-30HRC | | |
| | 60-70HRA | | |
| | 70-85HRA | | |
| | 85-95HRB | | |
| | 60-70HRB | | |
| | 45-55HRB (铜制) | | |
| | 30-40HRB(铜制) | | |
| | 20-30HRB(铜制) | | |
| | 90-100HRF | | |
| | 80-90HRF(铜制) | | |
| 标准 塑料 洛氏 硬度块 | 70-94HRE (铜制) | |  |
| | 100-120HRL (铜制) | | |
| | 85-100HRM (铜制) | | |
| | 114-125HRR (铜制) | | |
| 标准 表面洛氏 硬度块 | 88-92HR15N | |  |
| | 74-82HR30N | | |
| | 45-55HR30N | | |
| | 45-55HR45N | | |
| | 85-91HR15T | | |
| | 70-80HR30T | | |
| 标准 布氏 硬度块 | 54-72HR45T | |  |
| | 150-250HBW10/3000 | | |
| | 150-250HBW5/750 | | |
| | 150-250HBW2.5/187.5 | | |
| | 75-125HBW10/1000 | | |
| | 75-125 HBW5/250 | | |
| | 75-125HBW2.5/62.5 | | |
| | 250-350HBW10/3000 | | |
| 250-350HBW5/750 | | | |
| 250-350HBW2.5/187.5 | | | |
| 锤击布氏条 | 175-225HBW5/750 | | |
| 韦氏硬度块 | 10-20HW (铝制) | | |
| 标准巴氏块 | 82-88HBa | | |
| | 42-55HBa | | |
| 标准 维氏 硬度块 | 700-800HV3 | |  |
| | 700-800HV5 | | |
| | 700-800HV10 | | |
| | 700-800HV30 | | |
| | 700-800HV50 | | |
| | 400-600 HV5 | | |
| | 400-600HV10 | | |
| | 400-600 HV30 | | |
| | 175-225 HV5 | | |
| | 75-125HV3(铝制) | | |
| 75-125HV5(铝制) | | | |

| 产品名称 | 规格 | | | 图片 |
|-----------------|------------------|-----------------------|--|--|
| 标准 显微 硬度块 | 700-800 HV1 | | |  |
| | 700-800 HV0.5 | | | |
| | 700-800 HV0.3 | | | |
| | 700-800 HV0.2 | | | |
| | 400-600 HV0.2 | | | |
| | 400-600 HV0.1 | | | |
| | 175-225 HV0.1 | | | |
| | 175-225 HV0.05 | | | |
| | 175-225 HV0.025 | | | |
| | 75-150 HV0.1(铝制) | | | |
| 标准 努普 硬度块 | 700-800 HK1 | | |  |
| | 700-800 HK0.5 | | | |
| | 700-800 HK0.3 | | | |
| | 700-800 HK0.2 | | | |
| | 400-600 HK0.2 | | | |
| | 400-600 HK0.1 | | | |
| | 175-225 HK0.1 | | | |
| | 175-225 HK0.05 | | | |
| 标准 里氏 硬度块 | 750-850 HLD | | |  |
| | 590-670 HLD | | | |
| | 490-570 HLD | | | |
| | 550-630 HLG | | | |
| | 460-540 HLG | | | |
| 标准肖氏 硬度块 | 30±4HSD | | | <p style="text-align: center;">中国院证书</p> |
| | 60±4HSD | | | |
| | 90±4HSD | | | |
| 洛氏金刚石压头 | HRC, HRA | | | |
| 洛氏碳化钨钢球压头 | HRB (Ø 1.588) | | | |
| | | Ø12.7; Ø6.35; Ø3.175 | | |
| 布氏碳化钨压头 | | Ø10; Ø5; Ø2.5 | | |
| 碳化钨钢球 | | Ø10; Ø5; Ø2.5; Ø1.588 | | |
| | | Ø12.7; Ø6.35; Ø3.175 | | |

注： 以上均为常用规格，特殊要求订货另议。

需 方： _____
 地 址： _____
 电 话： _____
 传 真： _____
 开户银行： _____
 帐 号： _____
 税 号： _____
 邮 编： _____
 需方代表： _____
 手 机： _____

供 方： 南昌况氏硬度块制造有限公司 _____
 地 址： 南昌市高新区天祥大道佳海产业园 176 栋
 电 话： 0791-88436980 _____
 传 真： 0791-88436983 _____
 开户银行： 南昌市工行洪航支行 _____
 帐 号： 1502208109300002572 _____
 税 号： 91360104688507757P _____
 邮 编： 330024 _____
 供方代表： 况伟 _____
 手 机： 13617007929 _____
 网 址： www.NCKSYDK.COM _____
<http://ncksydk.cn.alibaba.com>
 E-mail: kuangwei1213@163.com _____
 品 牌： Kuang 况氏® _____